

PHOENIX **ZSU** ONLINE UPS

Critical Power Protection, Zero Downtime!

The new PHOENIX **ZSU** UPS offers flexibility, versatility & adaptability for critical applications in small & medium businesses worldwide.



Key Applications



Product Snapshot

Delivers An Outstanding Power Performance & Increased Power Quality

- True VFI | online double conversion design guarantees the complete isolation of critical load from any mains disturbances.
- Transformerless; high frequency, IGBT rectifier & inverter design via PWM technique presents active power factor correction at input which lowers THDi at input & maximizes the input power factor as > 0,996. This leads minimized generator : UPS sizing, less investment and costs due to very low harmonics. The system reduces the effect on utility and the loads connected to the same network with the ups itself. IGBT design at the inverter stage also brings high output power as 0,9 while reducing the THDv as low as 1%.
- Twin DSP microprocessor control offers maximized reliability, total protection of UPS & critical load against failures & damages, unbeatable parallel redundant operation in business-critical environments and applications.
- Transformerless design also brings a compact, lightweight design which brings ease of transport, installation and maximizes power density in minimum footprint as low as 0,05 m2 for a 1 kVA **ZSU** UPS
- Greater adaptability, versatility in system configurations, higher immunity to harmonics, sudden inrush currents & disturbances in utility power. Flexible & versatile to vast of applications & environments.

Controlling Both CAPEX and OPEX

- Delivers industry leading 95%* AC~AC online double-conversion efficiency without sacrificing reliability. Thanks to its highly efficient design, savings can reach up to 35% in dissipated energy in one year compared to traditional legacy UPS [87%] systems resulting in a faster payback period of 4 years as ROI.
- Ease of installation & deployment - for some models plug&play design-reduced cooling infrastructure requirement. Keeping power & cooling infrastructure cost at minimum [CAPEX] along with operating costs at minimum [OPEX], UPS **ZSU** gives the power of control.
- Scalability - Pay as You Grow! Capacity can flex to meet power infrastructure growth by adding an additional ups in the field whilst offering true redundancy, ease of expansion from small-sized installations to mid-sized infrastructures.

Power Protection! Affordable, Dependable!

The UPS **ZSU** is the premium of TSINE' s single phase PHOENIX UPS family thanks to its innovative DSP controlled, transformerless-high frequency, IGBT Rectifier & Inverter design.

PHOENIX **ZSU** offers extended power protection performance, increased power quality & continuous power for any type of small-mid range applications via its true online double conversion, voltage-frequency independent [VFI] design which isolates the critical output load against any failures and disturbances in utility power whilst powering it continuously by the inverter which supplies a sinusoidal voltage, filtered & conditioned in terms of voltage, form & frequency. Input and output filters provide significant further immunity from mains disturbances & lightning strikes.

The UPS **ZSU** is one of the best UPS systems available on the market with its efficiency values & power density, proven reliability and maximised availability which dramatically decrease operational downtimes and costs during its lifetime.

PHOENIX **ZSU** comes with standard communication, supervision & diagnosis features such as LCD display & RS232 as standard, USB, Dry Contact interfaces & network card as an option. The UPS **ZSU** is the smart choice for mission-critical applications requiring the highest levels of reliability.

Advanced Battery Care

The UPS PHOENIX **ZSU** provides extended service life for batteries via its IBC [Innovative Battery Care] Extendable scalable runtime feature of The UPS **ZSU** offers the ultimate solution for business continuity applications requiring long runtimes.

Reliability, Availability and Serviceability (RAS)

Maximized availability and reliability by the power engineering at its top level, PHOENIX **ZSU** offers very robust & reliable power protection, this also leads minimized downtime and highest level of availability. Very high level of MTBF [Mean Time Between Failures] and very low MTTR[Mean Time to Repair] ensures the critical load not to fail for its duty. Serviceability is a measure of the system to be recovered after a disaster.A min. of 15 mins. of enough for a technician to diagnose and recover the system to reduce the downtime for business.

UPS Rating

Rated Power [kVA]	1	2	3	6	10	15	20
Active Power [kW]	0,9	1,8	2,7	5,4	9	13,5	18 [0,9 Power Factor]

General Characteristics

MTBF/ MTTR	Over 225000 Hours/ Under 30 Minutes	
UPS Type & Technology	VFI Online Double Conversion [Complete Isolation of Output Load with Any Mains Disturbances] High Frequency Operation, IGBT Rectifier & Inverter, Transformerless Design Twin DSP Microprocessor Control via PWM Technique	
62040-3	COMPATIBLE	
Power Factor	0,9, Optional Unity PF, kVA=kW, 1,0	
Input Voltage Range	120 ~ 295 ±5 VAC	80 ~ 295 ±5 VAC [at 50% Rated Load]
True Redundancy	N+X, N+1 Redundant Configurations	
Parallel Configuration [N+1]	Up To 4 Units	
Standard Protection Features	Overload, Low Battery, Deep Discharge Protection, Input Power Limiting, Phase Reversal, Power Module Over Temperature, Over Current, High Temperature Alert, Smart Short Circuit, Load Current Limiting, Charging Current Limiting, Temperature Compensated Charging.	
Operating Conditions	20°C, <1000m Above Sea Level, <45% to 55% RH, for Best Performance	
Cooling/ Isolation	Forced Air Cooling via Redundant Fans, Smart Fan Speed Control 1-3 kVA LED Display: Utility or Bypass, Battery Low, Battery Abnormal, Overload, Site Wiring Fault, Service Mode, UPS Off, UPS Abnormal Parameters Shown on LCD: Input /Output Voltage and Frequency Values, Load%, Battery Voltage, Internal Temperature Alarms: Line Failure, Battery Low, Over Load, Failure Events 6*20 kVA LED & LCD Display: Line Mode, Backup Mode, ECO Mode, Bypass Supply, Battery Low, Battery Bad/Disconnect, Overload and Transferring with Interruption & UPS Fault Parameters Shown on LCD: Input Voltage, Input Frequency, Output Voltage, Output Current, Output Frequency, Load Percentage, Battery Voltage & Inner Temperature. Self Diagnostics: Upon Powering-on, Front Panel Setting & Software Control, 24-hour routine checking Audible & Visual Alarms: Line Failure, Battery Low, Transfer to Bypass, System Fault Conditions	
Display & Parameters		
Maintenance Bypass	STANDARD	
Material [Casing]/ Colour	BLACK	
Cable Entry	REAR/ FRONT BOTTOM	

Efficiency

AC~AC Mode	92%	92.5%	93.3%	95%	95%	95%	95%
Eco-Mode	≥ 98%			≥ 98%			
DC~AC/ Battery Mode	≥ 95%			≥ 96%			

Input

Rated Voltage & Range	208/ 220/ 230/ 240 VAC 1P+N+PE [Selectable via LCD]	
	[at 100% Rated Load]	145 ~ 295 ±5 VAC
	[at 50% Rated Load]	120 ~ 295 ±5 VAC
Rated Frequency & Range	50/60 Hz [Automatic Self Synchronization] 45-55 Hz ± 0,5% / 40-70 Hz ± 0,5%	
Power Factor	≥ 0,99 Active Power Factor Correction Circuitry	
Current Distortion [THDi]	< 5%	

Battery

Battery	Standard: 5 minutes (optional)						
Rated Voltage [DC]	24	48	72	192	192	192	192
Intelligent Battery Management	Temperature Compensated 4 Stage Charging, Deep Discharge Protection, Scheduled/Automatic & Manual Battery Test, Operating Temperature						
Charging Capacity	25% of Rated Power, 20°C - 25°C for Longer Battery Lifetime						

Output Characteristics

Rated Voltage & Accuracy	208/ 220/ 230/ 240 VAC 1P+N+PE [Selectable via LCD] < ±1% at 100% Rated Linear-Static Load, < ±2% at Non-Linear Load; < ±5% at Dynamic Loads	
Rated Frequency & Accuracy	50/ 60 Hz (Selectable), ±0,1 Hz (Synchronized to Mains) ±0,1 Hz (Battery Mode)	
Power Factor	0,9, Optional Unity PF, kVA=kW, 1,0	
Voltage Distortion [THDv]	< 2% at 100% Linear Load < 5% at Non-linear Load	< 1% < 4%
Waveform	Pure Sinewave	
Transfer Time	0 ms, From AC Mode to Battery Mode, Inverter to Bypass	
Cold Start	Standard, The UPS operated without AC Mains, on Battery Power	
Crest Factor	3:1	
Unbalanced Load & Acceptable Load PF	Compatible Operation on 100% Unbalanced Load 0,9 leading to 0,9 lagging	
Overload Operation	60 seconds @ 105% ~ 150% Rated Load; 300 milliseconds @ ≥ 150% Rated Load	10 minutes @ 105% ~ 125% Rated Load 60 seconds @ 125% ~150% Rated Load 100 milliseconds @ ≥ 150% Rated Load Switches to Bypass Line over 150% Rated Load

Static Bypass

Rated Voltage & Range	208/ 220/ 230/ 240 VAC 1P+N+PE Output Voltage ±32 VAC	160 VAC ~ OV ±32 VAC
Rated Frequency & Range	50/60 Hz, 47 ~ 53 Hz/ 57 ~ 63 Hz [Adjustable]	

Communication & Supervision

Remote Monitoring & Management	Standard (Available As Hardware & Software): RS232 Serial Comm. Port, SNMP Slot, USB slot, EPO (Emergency Power OFF) Button, Monitoring & Management Software. Optional (As Hardware, Standard in Software): Network Manager [SNMP] Monitoring & Management over Web Browser, USB, Dry Contacts [The Following Data Can Be Seen: UPS Failure, UPS Audible Alarm, GND, Remote Shutdown, Bypass Active, Low Battery, UPS On, Utility Failure], Remote Monitoring & Management Panel, TCP/IP converter, GSM/GPRS Modem, Communication Ports Multiplier.
--------------------------------	---

Environment

Operating Temperature Range	0°C - 40°C / 20°C - 25°C / -30°C ~ 60°C	
Prespecified Operating T.		
Storage Temperature		
Altitude/ Relative Humidity	< 2000m above sea level/ < 95% (non-condensing)	
Noise	< 50 dBA	< 55 dBA

Certifications

Safety	EN 62040-1	
Electromagnetic Compatibility [EMC]	EN 62040-2	
Performance [VFI-SS-111]	EN 62040-3	
Safety	EN 60950-1 Information Technology Equipment	
Quality Management	CE, ISO 9001:2015, ISO 14001:2015	

Optional Features & Accessories

Isolation Transformer	Optional for Input & Output	
Custom Input Voltage Range	Optional	
IP Classified Enclosure	Available from IP21 ~ IP 66	
Others	Paralleling Kit, Network Management Kit(Internal/ External), External Bypass, Remote Monitoring & Management Panel, UPS Looking Battery Enclosures...etc	

Physical

Dimensions [mm]	145*360*225 1 kVA 190*400*330 2-3kVA	230*502*553 6-10 kVA ask for 15-20 kVA
Weight [kg]	9.2 for 1 kVA 17.7 for 2 kVA 22.9 for 3 kVA	54.5 for 6 kVA 56.2 for 10 kVA ask for 15-20 kVA
Protection Degree	IP20 (Standard)	



TSINE ELEKTRONİK SANAYİ VE TİCARET LTD. ŞTİ.

Beyit St., No: 55, Yukarı Dudullu, Umraniye
P.O. BOX: 34775 İSTANBUL / TURKEY

+90 216 365 7049
+90 216 313 2970

info@tsinepower.com
www.tsinepower.com

For More Information on
The UPS PHOENIX SU,
Please Visit
www.tsinepower.com